



BV SERIES PRIMARY DISK HARROWS

SPECIFICATIONS:

STANDARD EQUIPMENT:

36" (910 mm) diameter, 12 mm thick, cutout (notched) deep concave, disk blades.

Hydraulic lift undercarriage I

OPTIONAL EQUIPMENT:

Disk blades:

- 32" x 3/8" Cutout (notched, deep concavity.
- 32" x 1/2" Cutout (notched), deep concavity.

Cylinder Rod Stops—all models



Model No.	Width of Cut*	No. of Disks	**Suggested		Wt. per disk Kgs	Net Weight Kgs
			DB. PP.	kW.		
BV12-36	2750	16	3538.02—4445.2	150	466	5600
BV16-36	3650	20	4127.69—5034.87	180	436	6980

* Widths may vary depending on selected disc spacing

* Drawbar Pounds Pull, PTO kW and Drawbar power are suggested ranges and vary according to soil conditions and weight added to harrow. Harrow weights shown are with standard 28" x 8mm thick, cutout, deep concavity disk blades.



Roadking
Manufacturing (Pty)Ltd

ENQUIRIES & ORDERS:

Office+27 (0) 86 033 3110

Cell +27 (0)824687094

info@roadkingsa.co.za

www.roadkingsa.co.za