




**MKULU 1440—40 M/3 Split Bin Silage Trailer**



**MKULU 1440—Underbody Twin lift Cylinder**



**MKULU 1440—Walking beam suspension**



**MKULU 1440— Sprung suspension option**

*Built and distributed by*

**Roadking**  
Manufacturing (Pty)Ltd

**ENQUIRIES & ORDERS:**

**+27 (0) 86 033 3110 Cell 0824687094**

**info@roadkingsa.co.za**

**www.roadkingsa.co.za**



## 1440 HARVEST TRAILER

### SPECIFICATIONS:

Bin Width :	2500 mm
Bin Height:	2700 mm
Bin Length:	6000 mm
Material	S355J 5mm deck 3mm sides
Overall Length:	7590 mm
TARE:	5800 Kg
Nominal Load:	14000 Kg
Volumetric	40 m/3
AXLE:	4 x 13 Ton 127mm round ABS stubs
BRAKES:	Hydraulic actuated
SUSPENSION:	Walking beam or J2 Henred Sprung
TYRES:	600/65x 22.5
HITCH:	60 mm Bugle eye coupler
TAILGATE:	Hydraulic top lift

### OPTIONAL

- *Hydraulic landing leg*
- *90mm ball type coupler*
- *Spare wheel*
- *Choice of tyres*
- *Pneumatic braking*
- *Sprung drawbar*
- *Grain Hatch*

### OVERVIEW

The industrial premium grade Mkulu 1440 infield Harvest series trailers are suitable for tractors from 115-150Kw and can be easily modified as to bin size or construction material, depending on the anticipated load. In addition, hitch & coupler types can be modified at time of manufacture to suit your operation. Standard Wheel fitment is 600/65X22.5 but as an option you may specify another tyre type for extended road use if required. Standard suspension fitment is our double pinion walking beam with 60mm High Carbon alloy centre cross shaft and greasable vesconite Bushing which is designed to handle difficult infield conditions. The Mkulu 1440 is supplied with twin multi stage single acting heavy duty underbody lift cylinders, hydraulically opening tailgate and automatic tailgate lock sys-